

L1 ANSWER 19 OF 301 CA COPYRIGHT 2006 ACS on STN
 AN 142:200601 CA
 ED Entered STN: 03 Mar 2005
 TI Method and device for capturing melting flying ash
 IN Kiribayashi, Toshimitsu; Ozawa, Saburo; Hashimoto, Eihiro; Yamada, Mitsuo;
 Iwami, Tsuneo
 PA Kyowa Exeo Corp., Japan
 SO Jpn. Kokai Tokkyo Koho, 13 pp.
 CODEN: JKXXAF
 DT Patent
 LA Japanese
 IC ICM B01D046-02
 ICS B01D053-50; B01D053-68; B01D053-81
 CC 47-2 (Apparatus and Plant Equipment)
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 2005034695	A2	20050210	JP 2003-197704	20030716
PRAI	JP 2003-197704		20030716		

CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
JP 2005034695	ICM	B01D046-02
	ICS	B01D053-50; B01D053-68; B01D053-81
	IPCI	B01D0046-02 [ICM,7]; B01D0053-50 [ICS,7]; B01D0053-68 [ICS,7]; B01D0053-81 [ICS,7]
	FTERM	4D002/AA02; 4D002/AA19; 4D002/AB01; 4D002/AC10; 4D002/BA03; 4D002/BA14; 4D002/CA11; 4D002/CA13; 4D002/DA05; 4D002/DA12; 4D002/EA02; 4D002/GA01; 4D002/GB01; 4D002/GB06; 4D002/GB12; 4D002/HA06; 4D058/JA04; 4D058/MA54; 4D058/NA10; 4D058/SA20; 4D058/TA02; 4D058/UA03; 4D058/UA10
AB	The method is characterized by being able to eliminate the filter clogging using reversed washing. <u>The fly ash, with an average particle size of 3.5-7.5 μm, from the waste gas of a combustion furnace is removed by using a bag filter.</u> The gas flow rate is controlled at 0.4-0.7 m/min. Slaked lime of 1.5-2 times of the acid gas in the waste gas is added to the gas flow before the bag filter for neutralization.	
ST	device capturing melting flying ash bag filter reversed washing	
IT	Filters	
	(bags; capturing melting flying ash from waste gas using	

→ treat fly ash
 from a combustion furnace
 has particle size 3.5-7.5 μ m
 well within applicant's claimed range
 of up to 10 μ m.